



TANQUES JUMBO

Los Tanques Jumbo son diseñados para almacenar Oxígeno, Nitrógeno, Argón en estado líquido, así como Gas Natural Licuado y Etileno.

20,000 a 93,500 Galones

PMT 50, 80, 125, 170, 270 lbs/pg2

Tanque interior: Acero inoxidable

Aislamiento Perilita

DATOS TECNICOS									
Modelo	35000	45000	50000	55000	60000	70000	75000	80000	935000
Volumen de agua @ 100% gal(L):	38168	49571	53372	59073	64775	76178	79979	85680	98984
	144482	187647	202035	223617	245200	288364	302753	324335	374694
Volumen en frío @ 95% gal(L):	35951	46692	50272	55643	61013	71754	75334	80704	93235
	136091	176749	190302	210631	230960	271618	285170	305499	352933
PMT Psig (kg/cm ²):	50 (3.51)		120 (8.43)	150 (10.54)	180 (12.65)	250 (17.57)			
Producto:	LIN / LOX / LAR / LNG / ETH								
Peso vacío ± 1 % lb (kg):	91342	113754	120368	123093	138358	155950	162592	171495	193023
	41432	51598	54598	55834	62758	70738	73751	77789	87554
Largo ft (m):	49.50	64.50	69.50	77.00	84.50	99.50	104.50	112.00	129.50
	15.09	19.66	21.18	23.47	25.76	30.33	31.85	34.14	39.47
Ancho ft (m):	13.67	13.67	13.67	13.67	13.67	13.67	13.67	13.67	13.67
	4.17	4.17	4.17	4.17	4.17	4.17	4.17	4.17	4.17
Alto ft (m):	13.04	13.04	13.04	13.04	13.04	13.04	13.04	13.04	13.04
	3.98	3.98	3.98	3.98	3.98	3.98	3.98	3.98	3.98
Porcentaje de evaporación (LOX)/dia menor que:	0.27 %	0.26 %	0.25 %	0.24%	0.23 %	0.22 %0	.21 %	0.20 %	0.20 %